

CABLE TIES

LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

2.5 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DACT 80-2.3-L	80 (3.1)	2.4 (.09)	17 (.68)	8.1 (18)	MS3367-4	DAG-50	1,000
	DACT100-2.5-L	100 (4.0)		21 (0.83)				
	DACT160-2.5-L	160 (6.2)	2.5 (.10)	40 (1.57)				
	DACT200-2.5-L	205 (8.0)		52 (2.02)				
3.6 TIE BODY WIDTH	DACT140-3.6-L	146 (5.7)	3.6 (.14)	35 (1.38)	17.8 (40)	MS3367-5	DAG-50	1,000
DACT200-3.6-L	203 (8.0)	50 (2.00)						
DACT210-3.6-L	210 (8.26)	52 (2.04)						
DACT300-3.6-L	300 (11.8)	77 (3.03)						
DACT370-3.6-L	370 (14.5)	102 (4.00)						

LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

4.8 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	DACT120-4.8-L	120 (4.7)	4.8 (.19)	30 (1.00)	22.2 (50)	MS3367-1	DAG-50	1,000
	DACT160-4.8-L	160 (6.2)		40 (1.57)		"		
	DACT190-4.8-L	190 (7.5)		48 (1.89)		"		
	DACT200-4.8-L	200 (8.0)		52 (2.05)		"		
	DACT250-4.8-L	250 (10.0)		67 (2.64)	MS3367-7	MS3367-7	MS3367-2	500
	DACT280-4.8-L	280 (11.0)		76 (2.99)				
	DACT300-4.8-L	300 (11.8)		83 (3.27)				
	DACT370-4.8-L	368 (14.5)		102 (4.02)				

Material : Nylon 66
 Color : Natural or Black(UV)
 Flammability: UL 94V-2 or UL94 V-0
 Service Temperature : 85°C

Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)

CABLE TIES

● LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

6.3 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia.(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
		DAMCT270-6.1-L	279 (10.5)	6.1 (.24)	73 (2.87)			
DAMCT300-6.3-L		300 (11.8)	6.3 (.24)	80 (3.15)	45.3 (100)	MS3367-3	DAG-250	300
DAMCT370-6.3-L		370 (14.5)	6.3 (.24)	102 (4.02)				
7.6 TIE BODY WIDTH	DAMCT200-7.6-L	200 (8.0)		50 (2.00)				500
	DAMCT300-7.6-L	300 (11.8)	7.6 (.30)	78 (3.07)	53.4kg (120)	MS3367-3	DAG-250	300
	DAMCT370-7.6-L	370 (14.5)		102 (4.02)				

● LOCKING CABLE TIES



(*)Suffix "-WR" should be added if black(outdoor) color is required.

9.0 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia.(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
		DAMCT450-9.0-L	455 (17.7)		127 (5.0)			
DAMCT530-9.0-L		530 (20.9)		152 (6.0)				
DAMCT650-9.0-L		650 (25.6)	9.0	188 (7.40)	77.8 (175)	MS3367-6	DAG-250	
DAMCT780-9.0-L		780 (30.6)	(.35)	225 (8.86)				
DAMCT880-9.0-L		880 (34.6)		260 (10.24)				
DAMCT1000-9.0-L		1000 (42.5)		320 (12.69)				

Material : Nylon 66
 Color : Natural or Black(UV)
 Flammability: UL 94V-2 or UL94 V-0
 Service Temperature : 85 °C

Most **Dong-A Cable Ties**, when tested, meet the requirements of **MIL-S-23190E** (or **SAE AS23190**)

CABLE TIES

EXTRA HEAVY LASHING TIES



Available only in Natural Color or Weather Resistant Black.

(*)Suffix "-WR" should be added if black(outdoor) color is required.

12.7 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	LOCKING TYPE Loop on the head Type	DAL300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250
DAL400-12.7-L		400 (15.7)	102 (4.02)					
DAL540-12.7-L		540 (21.3)	150 (5.91)					
DAL780-12.7-L		780 (30.7)	220 (8.66)					
RELEASABLE TYPE DARCT	DARCT300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250	100
	DARCT400-12.7-L	400 (15.7)		102 (4.02)				
	DARCT540-12.7-L	540 (21.3)		150 (5.91)				
	DARCT780-12.7-L	780 (30.7)		220 (8.66)				



Available only in Natural Color or Weather Resistant Black.

(*)Suffix "-WR" should be added if black(outdoor) color is required.

12.7 TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Military Standard Spec,	Installation TOOL Part No	Package Q' ty
	LOCKING TYPE DAL	DAL300-12.7-L	300 (11.8)	12.7 (.50)	70 (2.76)	110 (250)	MS3367-6	DAG-250
DAL400-12.7-L		400 (15.7)	102 (4.02)					
DAL540-12.7-L		540 (21.3)	150 (5.91)					
DAL780-12.7-L		780 (30.7)	220 (8.66)					

* 내한성(耐寒性) 재질 발주시는 "LT" 추가,
내열성(耐熱性) 재질 발주시는 "HR" 추가,
내후성(耐候性) 재질 발주시는 "WR" 추가 표시 바랍니다.
(i.e) 내한성 : DAL400-12.7-LT
내열성 : DAL300-12.7-HR
내후성 : DAL300-12.7-LWR
Service Temperature : 85°C

Most Dong-A Cable Ties, when tested, meet the requirements of MIL-S-23190E (or SAE AS23190)

CABLE TIES

● NYLON12 CABLE TIES



(*)Suffix "-BK" should be added if black color is required.

TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Installation TOOL Part No	Package Q' ty
3.6	DACT-N12-140-3.6	146 (5.7)	3.6 (0.14)	35 (1.38)	11.3 (25)	DAG-50	1,000
	DACT-N12-200-3.6	200 (5.7)		50 (2.00)			
4.8	DACT-N12-190-4.8	190 (7.5)	4.8 (.19)	48 (1.89)	18.1 (40)	DAG-50	1,000
	DACT-N12-200-4.6	200 (5.7)		50 (2.00)			
	DACT-N12-300-4.6	201 (11.8)		83 (3.27)			500
7.6	DACT-N12-300-7.6	300 (11.8)	7.6 (0.30)	78 (3.07)	40.8 (90)	DAG-250	100
	DACT-N12-370-7.6	370 (14.5)		102 (4.02)			
9.0	DACT-N12-450-9.0	455 (17.7)	9.0 (.35)	127 (5.00)	53.4 (120)	DAG-250	100
12.7	DACT-N12-400-12.7	400 (15.7)	12.7 (0.5)	102 (4.02)	77.8 (175)	DAG-250	50
	DACT-N12-540-12.7	540 (21.3)		150 (5.91)			

Material : Nylon 12

Excellent resistance to UV(ultraviolet), Overall Chemicals (hydrocarbons, chlorinated hydrocarbons, Acids, Bases) and Salts

● STAINLESS STEEL LOCK-KEY CABLE TIE



(*)Suffix "-BK" should be added if black color is required.



TIE BODY WIDTH	PART NO	Length mm (inch)	Width mm (inch)	Max Bundle Dia,(inch)	Tensile Strength Kg(LBS)	Installation TOOL Part No	Package Q' ty
3.6	DSLTL 155-3.6	155 (6.1)	3.6 (0.14)	38 (1.5)	17.8 (40)	DAG-50	1,000
	DSLTL 203-3.6	203 (8.0)		51 (2.0)			
4.7	DSLTL 203-4.7	203 (8.0)	4.7 (0.185)	51 (2.0)	22.2 (50)	DAG-50	1,000
	DSLTL 305-4.7	305 (12.0)		77 (3.0)			
7.0	DSLTL 300-7.0	300 (11.8)	7.0 (0.275)	77 (3.0)	53.4 (120)	DAG-250	100
	DSLTL 378-7.0	378 (14.9)		102 (4.0)			

Material : 66 Nylon

Color : Natural or Black(colors are available upon request)

Flammability: UL 94V-2 or UL94V-0

Service Temperature : 85 °C